

Product sheet Axis

Specifications:

Based on Product sheet No. 4

Series:	Axis	
Product description:	Non Woven Backed vinyl wallcovering Bio-Pruf™ treated	
Measurements:	Width:	± 106 cm ± 41 inch
	Roll Length:	± 35 mtr ± 38 yard
	Weight:	± 450 gr/m ² ± 20 oz

Application instruction:

Hanging instruction:	Non reverse/straight	Overlap and double cut
Pattern repeat:	64 cm	25.20 inch
Recommended adhesive:	BN Walls BK 10 for absorbing surfaces. BN Walls BK 30 for non-absorbing surfaces.	

Fire safety:

Euro Class:	B-s2-d0	EN 13501-1
IMO:	Available on request, subject to minimum order quantity	

Product features:

Light fastness:	≥ 7 International Woolscale - BS EN 20105 / ISO EN 105-B02
Resistant to:	Soap; detergents; alcohol; ammonia; alkali; diluted acids
Not resistant to:	Solvents like ketones; esters; aromatic hydrocarbons
Washability:	Extra-scrubbable (depends on embossing/structure) EN 259-1 / EN 12956
Durability:	Impact resistant according to EN 259-2
Other features:	Bio-Pruf™ treated to resist the growth of mold/mildew and odor causing microbes FSC™ certified: FSC-C100728 Reach compliant according to EU regulation 1907/2006EC
Made in EU:	CE Compliant – according to EN 15102:2007 + A1:2011 Details see Declaration of Performance 10

Services:

Warranty:	All Items are free of workmanship and mechanical defects under normal use and service of five years from date of delivery. This warranty applies only on professionally installed wallcoverings as advised in BN Walls hanging instructions
Customized:	Custom colours and design upon request, subject to minimum order quantity
Samples:	A4 samples are available on request
	Productsheets last revised: 08-09-2020



BN Walls
The Netherlands
info@bnwalls.com
bnwalls.com/professional

