

Product sheet wallcovering adhesive BK10

Specifications

Type:	Adhesive for absorbent surfaces
Composition:	Mixture of high-quality starches reinforced with an EVA copolymer

Properties

Appearance:	White paste
pH:	Approx 7,5
Solvents:	No. VOC content: < 1 gr./L. as a consequence of guideline 2004/42/EC
Coverage:	± 200 g/m ² , covers approximately 5 m ² per kilo (varies per backing and surface)
Open time:	± 20 min. max.
Drying time:	Minimum 24 hours or more depending on the temperature of the room and substrate
Shelf life:	± 18 months - in closed original packaging, cool and dry - protect from frost
Min. working temperature:	Ideal processing temperature >15°C. Do not process at a temperature of <5°C and / or a humidity of >70%.
Ecological information:	Contains no hazardous ingredients. Based on starch and polyvinylacetate in aqueous dispersion. Biologically degradable. Contains no heavy metals.

Directions

Preparation:	Stir well before use. Do not dilute. The wall should be flat, dry and clean; remove remnants of wallcovering and paint.
Application:	Apply the adhesive to the wall with a lambswool roller or a brush. Press the wallcovering firmly to the wall, and smooth down using a plastic spatula. Avoid getting adhesive on the surface of the wallcovering.
Cleaning storage:	Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tooling should be cleaned with water immediately after use.

Packaging and Transportation

Packaging:	Plastic buckets of 10 kg
Transportation:	Not classified as hazardous for transport. Transport by sea or land, not by air.
Storage conditions:	Keep dry, cool and closed in original packaging. Protect against frost.
Product sheet last revised:	01-05-2020



BN Walls

The Netherlands

info@bnwalls.com

bnwalls.com/professional