

Product sheet wallcovering primer BK15

Specifications

Type:	The product is not colored. The liquid is white and dries transparent colorless.
Composition:	The primer is based on a PVAc dispersion.

Properties

Appearance:	White liquid
pH:	Approx 5
Solvents:	No. VOC content: < 1 gr./L. as a consequence of guideline 2004/42/EC
Coverage:	± 100 g/m ² , covers approximately 10 m ² per kilo (varies per backing and surface)
Drying time:	Dust dry after about 3 hours. Can be wallpapered after about 24 hours.
Shelf life:	± 6 months - in closed original packaging, cool and dry - protect from frost
Min. working temperature:	+ 15°C
Ecological information:	The primer is based on a PVAc dispersion. Contains no hazardous ingredients. Based on vinylacetate co-polymer in aqueous dispersion. Partially biologically degradable. Contains no heavy metals.

Directions

Preparation:	Stir well before use. The wall should be flat, dry and clean; remove remnants of wallcovering and paint.
Application:	Apply the primer to the wall with a lambswool roller, a brush or by spraying.
Cleaning storage:	Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tooling should be cleaned with water immediately after use.

Packaging and Transportation

Packaging:	Plastic jerrycans of 5 L.
Transportation:	Not classified as hazardous for transport. Transport by sea or land, not by air.
Storage conditions:	Keep dry, cool and closed in original packaging. Protect against frost.
Product sheet last revised:	01-05-2020



BN Walls

The Netherlands

info@bnwalls.com

bnwalls.com/professional