

Product sheet wallcovering adhesive BK23

Specifications

Type: A starch/PVAC combination adhesive for bonding vinyl wallcovering with a paper backing and non woven backing up to ± 300 gr/m² on an absorbent surface. The adhesive is ready for use, also in wallpaper machines. Stir well before use.

Composition: Liquid wallcovering adhesive based on polyvinylacetate and starch.

Properties

Appearance: White, liquid adhesive

pH: Approx 7,5

Solvents: No. VOC content: < 1 gr./L. as a consequence of guideline 2004/42/EC

Coverage: $\pm 150 - 300$ g/m², covers approximately 6 - 3 m² per kilo (varies per backing and surface)

Open time: ± 30 min. max.

Drying time: Up to about 24 hours

Shelf life: ± 6 months - in closed original packaging, cool and dry - protect from frost

Min. working temperature: Ideal processing temperature >15°C. Do not process at a temperature of <5°C and / or a humidity of >70%.

Ecological information: Contains no hazardous ingredients. Based on starch and polyvinylacetate in aqueous dispersion. Biologically degradable. Contains no heavy metals.

Directions for use

Preparation: Stir well before use. Apply the paste with a pasting machine on the back of the material. The walls have to be flat, solid and thoroughly dry: free of grease and dust. Completely remove existing wallcoverings and paint marks.

Application: After pasting apply the wallcovering, the max. open time is about 30 minutes. Press the wallcovering firmly against the wall using a plastic smoother.

Cleaning storage: Close the joint and remove any paste that might have splashed onto the wallcovering with a sponge, or cloth dampened with clean water. Tools can be cleaned with water immediately after use.

Packaging and Transportation

Packaging: Plastic buckets of 12 kg

Transportation: Not classified as hazardous for transport. Transport by sea or land, not by air.

Storage conditions: Keep dry, cool and closed in original packaging. Protect against frost.

Product sheet last revised: 01-05-2020



BN Walls

The Netherlands

info@bnwalls.com

bnwalls.com/professional