

# Product sheet wallcovering adhesive BK30

## Specifications

---

**Type:** A ready mixed adhesive for hanging vinyl wallcoverings with textile or non-woven-backing onto non-absorbent surfaces or over existing vinyl. BK30 is waterproof and suitable for wet areas.

**Composition:** Polymer dispersion based on acrylate co-polymer.

## Properties

---

**Appearance:** Light brown paste

**pH:** Approx 7,5

**Solvents:** No. VOC content: < 1 gr./L. as a consequence of guideline 2004/42/EC.

**Coverage:** ± 250 g/m<sup>2</sup>, covers approximately 4 m<sup>2</sup> per kilo (varies per backing and surface)

**Open time:** ± 15 min. max.

**Drying time:** Minimum 24 hours, depending on substrate full drying can take up to a week.

**Shelf life:** ± 6 months - in closed original packaging, cool and dry - protect from frost

**Min. working temperature:** Ideal processing temperature >15°C. Do not process at a temperature of <5°C and / or a humidity of >70%.

**Ecological information** Contains no hazardous ingredients. Based on polymer and filler aqueous dispersion. Partially biologically degradable. Contains no heavy metals.

## Directions for use

---

**Preparation:** Stir well before use. Do not dilute. The wall should be flat, dry and clean; remove remnants of wallcovering and paint.

**Application:** Apply the adhesive to the wall with a lambswool roller or a brush. Press the wallcovering firmly to the wall, using a plastic spatula. Avoid getting adhesive on the surface of the wallcovering.

**Cleaning storage:** Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tooling should be cleaned with water immediately after use.

## Packaging and Transportation

---

**Packaging:** Plastic buckets of 10 kg.

**Transportation:** Not classified as hazardous for transport. Transport by sea or land, not by air.

**Storage conditions:** Keep dry, cool and closed in original packaging. Protect against frost.

**Product sheet last revised:** 01-05-2020



**BN Walls**

The Netherlands

info@bnwalls.com

bnwalls.com/professional