

# Product sheet Durafort PB300

## Specifications:

Based on Product sheet No. 05

Series:	Durafort PB300		
Product description:	BN Walls Contract – Paper Backed Vinyl Wallcovering		
Measurements:	Weight:	± 300 gr/m <sup>2</sup>	± 13 oz
	Width:	± 130 cm	± 51 inch
	Roll Length:	± 50 m	± 54 yd

**B  
N**  
WALLS

## Application instruction:

Hanging instruction:	See roll label	Overlap and double cut
Pattern repeat:	Depends on Design / x cm	x inch
Recommended adhesive:	BN Walls BK 10 for absorbing surfaces.	BN Walls BK 30 for non-absorbing surfaces.

## Fire safety:

Euro Class:	C-s2,d0	EN 13501-1
-------------	---------	------------

## Product features:

Light fastness:	≥ 7 International Wool scale	EN ISO 105-B02
Resistant to:	Soap; detergents; alcohol; ammonia; alkali; diluted acids	
Not resistant to:	Solvents like ketones; esters; aromatic hydrocarbons	
Washability:	Extra-scrubbable (depends on embossing/structure)	EN 259-1 / EN 12956
Durability:	Impact resistant according to	EN 259-2
Other features:	FSC™ certified: FSC-C100728 Non Phthalate Reach compliant according to EU regulation 1907/2006EC	
Made in EU:	CE – UKCA Compliant – according to EN 15102:2007 + A1:2011 Details see Declaration of Performance: DOP09 – DOP UK09	

## Services:

Warranty:	All Items are free of workmanship and mechanical defects under normal use and service of five years from date of delivery. This warranty applies only on professionally installed wallcoverings as advised in BN Walls hanging instructions
Customized:	Custom colours and design upon request, subject to minimum order quantity
Samples:	A4 samples are available on request
	Product sheet last revised: 10-2023

**B  
N**  
INTERNATIONAL

**BN International B.V.**

Rokerijweg 5  
1271AH Huizen  
The Netherlands  
+31 35 52 64 442

info@bninternational.com  
bnwalls.com/professional



Made in EU

<b>CE</b> 0493	<b>UK CA</b> 8515
23 DOP 09	23 DOP UK09
0493-CPR-W024 8515-CPR-W024	
EN 15102:2007 +A1:2011	