

Product sheet Flax

Specifications:

Based on Product sheet No. 08

Series:	Flax	
Product description:	BN Walls Contract – HT Non Woven Fabric Backed Vinyl Wallcovering Bio-Pruf™ treated	
Measurements:	Weight:	± 450 gr/m² ± 20 oz
	Width:	± 106 cm ± 41 inch
	Roll Length:	± 35 m ± 38 yd

BN
WALLS

Application instruction:

Hanging instruction:	See roll label	Overlap and double cut
Pattern repeat:	0 cm	0 inch
Recommended adhesive:	BN Walls BK 10 for absorbing surfaces.	BN Walls BK 30 for non-absorbing surfaces.

Fire safety:

Euro Class:	B-s2,d0	EN 13501-1
US Class:	Class A – Type II	ASTM E84-21a – Fed.Spec CCC-W-408D

Product features:

Light fastness:	≥ 7 International Wool scale	EN ISO 105-B02
Resistant to:	Soap; detergents; alcohol; ammonia; alkali; diluted acids	
Not resistant to:	Solvents like ketones; esters; aromatic hydrocarbons	
Washability:	Extra-scrubbable (depends on embossing/structure)	EN 259-1 / EN 12956
Durability:	Impact resistant according to	EN 259-2
Other features:	Bio-Pruf™ treated to resist the growth of mold/mildew and odor causing microbes FSC™ certified: FSC-C100728 Non Phthalate Reach compliant according to EU regulation 1907/2006EC	
Made in EU:	CE – UKCA Compliant – according to EN 15102:2007 + A1:2011 Details see Declaration of Performance: DOP16 – DOP UK16	

Services:

Warranty:	All Items are free of workmanship and mechanical defects under normal use and service of five years from date of delivery. This warranty applies only on professionally installed wallcoverings as advised in BN Walls hanging instructions
Customized:	Custom colours and design upon request, subject to minimum order quantity
Samples:	A4 samples are available on request
	Product sheet last revised: 09-2023

BN
INTERNATIONAL

BN International B.V.
Rokerijweg 5
1271AH Huizen
The Netherlands
+31 35 52 64 442

info@bninternational.com
bnwalls.com/professional



Made in EU

CE 0493	UKCA 8515
23 DOP 16	23 DOP UK16
0493-CPR-W030 8515-CPR-W030	
EN 15102:2007 +A1:2011	