

# Product sheet Infinity

## Specifications:

Based on Product sheet No. 01

Series:	Infinity		
Product description:	BN Walls Contract – Textile Backed Vinyl Wallcovering Bio-Pruf™ treated		
Measurements:	Weight:	± 360 gr/m <sup>2</sup>	± 15 oz
	Width:	± 130 cm	± 51 inch
	Roll Length:	± 50 m	± 54 yd

**BN**  
WALLS

## Application instruction:

Hanging instruction:	See roll label	Overlap and double cut
Pattern repeat:	0 cm	0 inch
Recommended adhesive:	BN Walls BK 10 for absorbing surfaces.	BN Walls BK 30 for non-absorbing surfaces.

## Fire safety:

Euro Class:	B-s2,d0	EN 13501-1
-------------	---------	------------

## Product features:

Light fastness:	≥ 7 International Wool scale	EN ISO 105-B02
Resistant to:	Soap; detergents; alcohol; ammonia; alkali; diluted acids	
Not resistant to:	Solvents like ketones; esters; aromatic hydrocarbons	
Washability:	Extra-scrubbable (depends on embossing/structure)	EN 259-1 / EN 12956
Durability:	Impact resistant according to	EN 259-2
Other features:	Bio-Pruf™ treated to resist the growth of mold/mildew and odor causing microbes Reach compliant according to EU regulation 1907/2006EC	
Made in EU:	CE – UKCA Compliant – according to EN 15102:2007 + A1:2011 Details see Declaration of Performance: DOP12 – DOP UK12	

## Services:

Warranty:	All Items are free of workmanship and mechanical defects under normal use and service of five years from date of delivery. This warranty applies only on professionally installed wallcoverings as advised in BN Walls hanging instructions
Customized:	Custom colours and design upon request, subject to minimum order quantity
Samples:	A4 samples are available on request
Product sheet last revised: 10-2023	

**BN**  
INTERNATIONAL

**BN International B.V.**  
Rokerijweg 5  
1271AH Huizen  
The Netherlands  
+31 35 52 64 442

info@bninternational.com  
bnwalls.com/professional



**Bio-Pruf™**

Made in EU

<b>CE</b> 0493	<b>UKCA</b> 8515
23 DOP 12	23 DOP UK12
0493-CPR-W027 8515-CPR-W027	
EN 15102:2007 +A1:2011	