Product sheet Ravi

Specifications:

Based on Product sheet No. 04

Series: Ravi

Product description: BN Walls Contract – Non Woven Fabric Backed Vinyl Wallcovering Bio-Pruf™ treated

Measurements: Weight: $\pm 450 \text{ gr/m}^2$ $\pm 20 \text{ oz.}$

Width: $\pm 106 \text{ cm}$ $\pm 41 \text{ inch}$ Roll Length: $\pm 35 \text{ m}$ $\pm 38 \text{ yd}$

- IN

Application instruction:

Hanging instruction: See roll label Overlap and double cut

Pattern repeat: 3 cm 1,2 inch

Recommended adhesive:

BN Walls BK 10 for absorbing surfaces. BN Walls BK 30 for non-absorbing surfaces.

Fire safety:

Euro Class: B-s2,d0 EN 13501-1

Product features:

Light fastness: ≥ 7 International Wool scale EN ISO 105-B02

Resistant to: Soap; detergents; alcohol; ammonia; alkali; diluted acids

Not resistant to: Solvents like ketones; esters; aromatic hydrocarbons

Washability: Extra-scrubbable (depends on embossing/structure) EN 259-1 / EN 12956

Durability: Impact resistant according to EN 259-2

Other features: Bio-Pruf™ treated to resist the growth of mold/mildew and odor causing microbes

FSC™ certified: FSC-C100728

Non Phthalate

Reach compliant according to EU regulation 1907/2006EC

Made in EU: CE – UKCA Compliant – according to EN 15102:2007 + A1:2011

Details see Declaration of Performance: DOP10 – DOP UK10

Services:

Warranty: All Items are free of workmanship and mechanical defects under normal use and service of five years

from date of delivery. This warranty applies only on professionally installed wallcoverings as advised in

BN Walls hanging instructions

Customized: Custom colours and design upon request, subject to minimum order quantity

Samples: A4 samples are available on request

Product sheet last revised: 10-2023

BNINTERNATIONAL

BN International B.V. Rokerijweg 5 1271AH Huizen

The Netherlands +31 35 52 64 442

info@bninternational.com bnwalls.com/professional





20 21
DOP 10 DOP UK10
EN 15102:2007 +A1:2011